## Aquasource Performance Data

Multipure's Aquasource System is certified by IAPMO R&T to NSF/ANSI 42 (Aesthetic Effects) for the reduction of Chlorine, Taste & Odor. Multipure drinking water systems are designed to be used where the water is microbiologically safe and has been adequately disinfected.

## NSF/ANSI 42 - Aesthetic Effects



Multipure's Aquasource has been certified by IAPMO R&T according to NSF/ANSI Standard 42 for the reduction of the following substances. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system.

Contaminant	Average Percent Reduction	Influent challenge concentration (mg/L unless specified)	Maximum permissible product water concentration (mg/L unless specified)
CHLORINE	86.6%	2.0 ± 10%	≥ 50%

## **Footnotes**

- 1. Do not use with water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system.
- 2. Multipure's Aquasource has been certified, as indicated, by IAPMO for compliance to NSF/ANSI Standard No. 42.
- 3. Filter life will vary in proportion to the amount of water used and the level of impurities in the water being processed. For optimum performance, it is essential that the filter be replaced on a regularly scheduled basis as follows: (a) annually; (b) when the system's rated capacity has been reached; (c) when the flow rate diminishes; or (d) when the filter becomes saturated with bad tastes and odors.
- 4. Do not allow water to freeze in the system. If the system is exposed to freezing temperatures, drain all water from the system and remove the filter.
- 5. Do not allow water to sit in the system for extended periods of time (10 or more days) without being used. If the system is to be left unused for more than 10 days, drain all water from the system and remove the filter. Upon your return, reconnect the filter in the housing/pressure vessel and continue use. In the event that water sits in the system for 10 or more days, the system should be flushed by allowing water to flow to waste for 10 minutes; after the system is flushed, resume use as normal.
- 6. Multipure system housings are warranted for a Lifetime (provided that the filter is replaced at least once a year). All exterior hoses and attachments to the system are warranted for defects in material and workmanship for one year. Please see the Owner's Manual for complete product guarantee and warranty information.
- 7. Please see the Owner's Manual for operating procedures.
- 8. In compliance with New York law, it is recommended that before purchasing a water treatment system, NY residents have their water supply tested to determine their actual water treatment needs. Please compare the capabilities of the Multipure system with your actual water treatment needs.
- 9. While testing was performed under standard laboratory conditions, actual performance may vary.
- 10. The list of substances which the treatment device reduces does not necessarily mean that these substances are present in your tap water.
- 11. The system and installation must comply with state and local laws and regulations.
- 12. The system is not intended for use converting raw sewage or other waste/refuse sources



7251 Cathedral Rock Drive, Las Vegas, NV 89128 702.360.8880

www.multipure.com